

## 2MP IR BULLET NETWORK CAMERA

### Short Description

The DS-2CD1023G0E-I is a 2MP IP bullet security camera designed for reliable indoor and outdoor surveillance. It features Full HD 1080p video recording, H.265+ video compression for efficient storage, up to 30m IR night vision, Digital WDR for clear backlight imaging, and IP67 weatherproof protection. The camera supports PoE (Power over Ethernet) for easy installation and delivers stable day/night monitoring for homes, offices, shops, and commercial security systems.



### Key Feature

- Model Number: DS-2CD1023G0E-I
- Brand: Hikvision
- Category: Internet Protocol (IP) Camera
- Availability: Available

### Product Information

<b>Model Number</b>	DS-2CD1023G0E-I
<b>Brand</b>	Hikvision
<b>Category</b>	Internet Protocol (IP) Camera
<b>Availability</b>	Available
<b>Price Type</b>	Contact for price

## Description

---

- 2 MP Full HD IP Bullet Camera
- 1/2.7" Progressive Scan CMOS image sensor
- Maximum resolution: 1920 × 1080
- Minimum illumination: 0.01 Lux (Color), 0 Lux with IR
- IR cut filter with automatic Day/Night switching
- Smart IR night vision up to 30 meters
- 850 nm infrared wavelength
- Available lens options: 2.8 mm and 4 mm fixed lens
- Wide viewing angle up to 112.1° horizontal FOV
- Fixed iris with F2.0 aperture
- Supports H.265+, H.265, H.264+, and H.264 compression
- Main stream up to 30 fps at Full HD resolution
- Sub-stream support for optimized remote viewing
- Digital WDR for balanced lighting performance
- 3D DNR and BLC image enhancement technologies
- Adjustable brightness, contrast, saturation, and sharpness
- Motion detection and video tampering alarm support
- Event notification via FTP, email, and surveillance center
- Supports ONVIF and ISAPI protocols
- Compatible with Hik-Connect and iVMS-4200 software
- Supports IPv4/IPv6, RTSP, HTTPS, SSL/TLS, and more
- Up to 32 user accounts with 3 permission levels
- Simultaneous live view up to 6 channels
- RJ45 10/100 Mbps Ethernet interface
- Supports 12V DC and PoE (802.3af Class 3) power supply
- Maximum power consumption: 6.5 W
- Pan: 0°-360°, Tilt: 0°-180°, Rotate: 0°-360°
- Operating temperature: -30°C to 60°C
- Humidity tolerance up to 95% non-condensing
- Compact and lightweight bullet design
- Supports privacy mask, watermark, anti-flicker, and IP filtering
- Suitable for indoor and outdoor surveillance applications