2MP SMART HYBRID LIGHT TURRET NETWORK CAMERA WITH AUDIO & STROBE LIGHT ALARM



Short Description

The Hikvision DS-2CD1323G2-LIUF/SL is a powerful yet affordable turret network camera designed for modern security needs. Featuring Smart Hybrid Light technology, it automatically switches between IR and white light — combining night-time clarity with active deterrence illumination up to 30 m. With intelligent detection, two-way audio, and robust weatherproofing, it's an ideal solution for homes, small businesses, and commercial properties.

Key Feature

- Model Number: DS-2CD1323G2-LIUF/SL
- Brand: Hikvision
- Category: Internet Protocol (IP) Camera
- Availability: Available

Product Information

Model Number	DS-2CD1323G2-LIUF/SL
Brand	Hikvision
Category	Internet Protocol (IP) Camera
Availability	Available
Price Type	Contact for price

Description

The DS-2CD1323G2-LIUF/SL is a powerful 2MP Full HD dome network camera designed to provide advanced security monitoring with intelligent detection and active deterrence features. Equipped with a high-performance Progressive Scan CMOS sensor, the camera captures clear and detailed 1920 × 1080 resolution video for reliable surveillance in both indoor and outdoor environments. Its Smart Hybrid Light technology combines infrared and white light illumination, enabling clear color images at night and providing visibility up to 30 meters in low-light conditions. Powered by Hikvision's AcuSense technology, the camera can accurately distinguish human and vehicle targets from other moving objects, significantly reducing false alarms caused by rain, animals, shadows, or leaves. The built-in microphone allows audio recording alongside video, providing additional evidence and situational awareness. For enhanced security, the camera features an active strobe light and audio alarm that can automatically deter intruders when unauthorized activity is detected.

The camera supports advanced H.265+ video compression, helping reduce bandwidth consumption and storage requirements without compromising image quality. Image enhancement technologies such as Digital WDR, BLC, and 3D DNR ensure clear footage in challenging lighting conditions. Remote access through Hik-Connect and iVMS-4200 software allows users to monitor their property from anywhere using a smartphone, tablet, or computer.

Designed for durability and long-term performance, the DS-2CD1323G2-LIUF/SL features an IP67-rated weatherproof housing, making it suitable for harsh outdoor environments. With support for PoE and 12V DC power options, flexible installation, ONVIF compatibility, and robust cybersecurity features, this camera is an ideal solution for homes, offices, retail stores, warehouses, schools, parking areas, and other commercial security applications.

Technical Specifications

Camera Specifications	
Image Sensor	1/2.9" Progressive Scan CMOS
Max. Resolution	1920 × 1080
Min. Illumination	Color: 0.005 Lux (F1.6, AGC ON) / B&W: 0 Lux with IR
Lens Type	Fixed focal, 2.8 mm or 4 mm
Supplement Light	IR + White Light (Smart Hybrid), up to 30 m
Compression	H.265+ / H.265 / H.264+ / H.264
Network	
Security	Password protection, complicated password, watermark, basic and digest authentication for HTTP, WSSE and digest authentication for Open Network Video Interface, security audit log, host authentication (MAC address)
Simultaneous Live View	Up to 6 channels
Protocols	TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, RTCP, NTP, IGMP, IPv4, IPv6, UDP, QoS, FTP, SMTP
Client	iVMS-4200,Hik-Connect
Web Browser	Plug-in required live view: IE 10, IE 11, Local service: Chrome 57.0+, Firefox 52.0+, Edge 89+
Interface	
Ethernet Interface	1 RJ45 10 M/100 M self-adaptive Ethernet port
Reset Key	Yes
Built-in Microphone	Yes
Power & Physical	
Power	12 VDC ± 25%, 0.66 A, max. 8 W,Ø5.5 mm coaxial power plug,reverse polarity protection, PoE: IEEE 802.3af, Class 3, max. 9.5 W

Material	Metal & Plastic