4 MP SMART HYBRID LIGHT FIXED BULLET NETWORK CAMERA



Short Description

The Hikvision DS-2CD1043G2-LIU is a 4MP Smart Hybrid Light Fixed Bullet Network Camera designed to deliver clear and reliable surveillance day and night. Equipped with advanced imaging technology, built-in microphone, and Smart Hybrid Light, it provides excellent security performance for residential and commercial environments.

Key Feature

- Model Number: DS-2CD1043G2-LIU
- Brand: Hikvision
- Category: Internet Protocol (IP) Camera
- Availability: Available

Product Information

Model Number	DS-2CD1043G2-LIU
Brand	Hikvision
Category	Internet Protocol (IP) Camera
Availability	Available
Price Type	Contact for price

Description

The Hikvision DS-2CD1043G2-LIU is a high-performance 4MP IP bullet camera engineered for dependable video surveillance. Featuring a 1/3-inch progressive scan CMOS sensor, the camera captures high-resolution images with exceptional clarity and detail.

Its Smart Hybrid Light technology automatically switches between infrared and white light illumination to provide clear images even in low-light conditions. The built-in microphone enables real-time audio recording for enhanced monitoring and evidence collection.

With H.265+ video compression, the camera significantly reduces bandwidth and storage requirements while maintaining superior image quality. Its weather-resistant design makes it suitable for both indoor and outdoor installations, ensuring continuous protection for homes, offices, warehouses, retail stores, and other commercial facilities.

The DS-2CD1043G2-LIU supports Power over Ethernet (PoE), simplifying installation by transmitting power and data through a single cable. Combining advanced imaging, audio capability, and intelligent lighting, this camera offers a reliable and cost-effective security solution.

Technical Specifications

Camera Specifications	
Image Sensor	1/3" Progressive Scan CMOS
Max. Resolution	2560 × 1440
Min. Illumination	Color: 0.005 Lux @ (F1.6, AGC ON),B/W: 0 Lux with IR
Shutter Time	1/3 s to 1/100,000 s
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°,tilt: 0° to 90°,rotate: 0° to 360°
Lens	
Lens Type	Fixed focal lens, 2.8 and 4 mm optional
Focal Length & FOV	2.8 mm, horizontal FOV 98°, vertical FOV 54°, diagonal FOV 114° 4 mm, horizontal FOV 78°, vertical FOV 42°, diagonal FOV 93°
Lens Mount	M12
Iris Type	Fixed
Aperture	F1.6
Illuminator	
Supplement Light Type	IR,White Light
Supplement Light Range	Up to 30 m
Smart Supplement Light	Yes
IR Wavelength	850 nm
Video	
Main Stream	50 Hz: 20 fps (2560 × 1440) 25 fps (1920 × 1080, 1280 × 720) 60 Hz: 20 fps (2560 × 1440) 24 fps (1920 × 1080, 1280 × 720)

Sub-Stream	50 Hz: 25 fps (1280 × 720, 640 × 480, 640 × 360) 60 Hz: 24 fps (1280 × 720, 640 × 480, 640 × 360)
Video Compression	Main stream: H.265+/H.265/H.264+/H.264, Sub-stream: H.265/H.264/MJPEG
Video Bit Rate	32 Kbps to 8 Mbps
H.264 Type	Baseline Profile,Main Profile,High Profile
H.265 Type	Main Profile
Bit Rate Control	CBR,VBR
Region of Interest (ROI)	1 fixed region for main stream
Audio	
Audio Type	Mono sound
Environment Noise Filtering	Yes
Audio Sampling Rate	8 kHz/16 kHz
Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC-LC
Network	
Security	Password protection, complicated password, watermark, basic and digest authentication for HTTP, WSSE and digest authentication for Open Network Video Interface, security audit log, host authentication (MAC address)
Simultaneous Live View	Up to 6 channels
Protocols	TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP
User/Host	Up to 32 users 3 user levels: administrator, operator, and user
Client	iVMS-4200,Hik-Connect
Web Browser	Plug-in required live view: IE 10, IE 11, Local service: Chrome 57.0+, Firefox 52.0+
Image	

Wide Dynamic Range (WDR)	120 dB
SNR	≥ 52 dB
Day/Night Switch	Day,Night,Auto,Schedule
Image Enhancement	BLC,HLC,3D DNR
Image Settings	Rotate mode,saturation,brightness,contrast,sharpness,gain,white balance,adjustable by client software or web browser
Privacy Mask	4 programmable polygon privacy masks
Interface	
Ethernet Interface	1 RJ45 10 M/100 M self-adaptive Ethernet port
On-Board Storage	-F: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB
Built-in Microphone	Yes
Event	
Basic Event	Motion detection (support alarm triggering by specified target types (human and vehicle)),video tampering alarm,exception
Linkage	Upload to FTP/memory card (-F), send email, notify surveillance center, trigger recording (-F), trigger capture
General	
Power	12 VDC ± 25%, 0.4 A, max. 5 W,Ø5.5 mm coaxial power plug,reverse polarity protection, PoE: IEEE 802.3af, Class 3, max. 6.5 W
Material	Metal & Plastic
Dimension	170.8 mm × 66 mm × 69.1 mm (6.7" × 2.6" × 2.7")