

4 MP SMART HYBRID LIGHT FIXED TURRET NETWORK CAMERA WITH AUDIO & STROBE LIGHT ALARM

Short Description

The Hikvision DS-2CD1343G2-LIUF/SL is a 4MP Smart Hybrid Light Fixed Turret Network Camera featuring built-in audio, active deterrence with strobe light and siren, and advanced low-light imaging. It delivers reliable security monitoring for residential and commercial applications.



Key Feature

- Model Number: DS-2CD1343G2-LIUF/SL
- Brand: Hikvision
- Category: Internet Protocol (IP) Camera
- Availability: Available

Product Information

| | |
|---------------------|-------------------------------|
| Model Number | DS-2CD1343G2-LIUF/SL |
| Brand | Hikvision |
| Category | Internet Protocol (IP) Camera |
| Availability | Available |
| Price Type | Contact for price |

Description

The Hikvision DS-2CD1343G2-LIUF/SL is a professional-grade 4MP IP turret camera designed to provide enhanced security with intelligent monitoring features. Equipped with a high-performance CMOS sensor, the camera captures crystal-clear images with excellent detail and color accuracy.

Its Smart Hybrid Light technology combines infrared and white light illumination to ensure clear footage in darkness while maintaining full-color images when needed. The built-in microphone enables synchronized audio recording for improved event verification.

This model also features active deterrence capabilities with an integrated strobe light and siren alarm that help discourage intruders and enhance site protection. With H.265+ compression technology, the camera minimizes storage and bandwidth usage while maintaining high image quality.

The weather-resistant housing allows reliable operation in both indoor and outdoor environments, making it suitable for homes, offices, retail stores, warehouses, schools, and other commercial facilities. Power over Ethernet (PoE) support simplifies installation by delivering power and data through a single network cable.

Technical Specifications

| Camera Specifications | |
|------------------------------|--|
| Image Sensor | 1/3" Progressive Scan CMOS |
| Max. Resolution | 2560 × 1440 |
| Min. Illumination | Color: 0.005 Lux @ (F1.6, AGC ON),B/W: 0 Lux with IR |
| Day & Night | IR cut filter |
| Angle Adjustment | Pan: 0° to 360°,tilt: 0° to 75°,rotate: 0° to 360° |
| Lens | |
| Lens Type | Fixed focal lens, 2.8 and 4 mm optional |
| Focal Length & FOV | 2.8 mm, horizontal FOV 98°, vertical FOV 54°, diagonal FOV 114° 4 mm, horizontal FOV 78°, vertical FOV 42°, diagonal FOV 93° |
| Lens Mount | M12 |
| Iris Type | Fixed |
| Aperture | F1.6 |
| Illuminator | |
| Supplement Light Type | IR,White Light |
| Supplement Light Range | Up to 30 m |
| Smart Supplement Light | Yes |
| IR Wavelength | 850 nm |
| Video | |
| Main Stream | 50 Hz: 20 fps (2560 × 1440) 25 fps (1920 × 1080, 1280 × 720) 60 Hz: 20 fps (2560 × 1440) 24 fps (1920 × 1080, 1280 × 720) |
| Sub-Stream | 50 Hz: 25 fps (1280 × 720, 640 × 480, 640 × 360) 60 Hz: 24 fps (1280 × 720, 640 × 480, 640 × 360) |

| | |
|-----------------------------|--|
| Video Compression | Main stream: H.265+/H.265/H.264+/H.264, Sub-stream: H.265/H.264/MJPEG |
| Video Bit Rate | 32 Kbps to 8 Mbps |
| H.264 Type | Baseline Profile,Main Profile,High Profile |
| H.265 Type | Main Profile |
| Bit Rate Control | CBR,VBR |
| Region of Interest (ROI) | 1 fixed region for main stream |
| Scalable Video Coding (SVC) | H.264 and H.265 encoding |
| Audio | |
| Audio Type | Mono sound |
| Audio Sampling Rate | 8 kHz/16 kHz |
| Environment Noise Filtering | Yes |
| Audio Compression | G.711/G.722.1/G.726/MP2L2/PCM/AAC-LC |
| Audio Bit Rate | 64 Kbps (G.711ulaw/G.711alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 192 Kbps (MP2L2)/16 to 64 Kbps (AAC-LC) |
| Network | |
| Security | Password protection, complicated password, watermark, basic and digest authentication for HTTP, WSSE and digest authentication for Open Network Video Interface, security audit log, host authentication (MAC address) |
| Simultaneous Live View | Up to 6 channels |
| API | Open Network Video Interface (Profile S, Profile T, Profile G),ISAPI,SDK |
| Protocols | TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, RTCP, NTP, IGMP, IPv4, IPv6, UDP, QoS, FTP, SMTP |
| User/Host | Up to 32 users 3 user levels: administrator, operator, and user |
| Client | iVMS-4200,Hik-Connect |

| | |
|--------------------------|---|
| Web Browser | Plug-in required live view: IE 10, IE 11, Local service: Chrome 57.0+, Firefox 52.0+, Edge 89+ |
| Image | |
| Wide Dynamic Range (WDR) | 120 dB |
| SNR | ≥ 52 dB |
| Day/Night Switch | Day,Night,Auto,Schedule |
| Image Enhancement | BLC,HLC,3D DNR |
| Image Settings | Rotate mode,saturation,brightness,contrast,sharpness,gain,white balance,adjustable by client software or web browser |
| Privacy Mask | 4 programmable rectangle privacy masks |
| Interface | |
| Ethernet Interface | 1 RJ45 10 M/100 M self-adaptive Ethernet port |
| On-Board Storage | Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB |
| Built-in Microphone | Yes |
| Built-in Speaker | Max. power consumption: 1.5 W, max. sound pressure level: 10 cm: 95 dB. |
| Reset Key | Yes |
| Event | |
| Basic Event | Motion detection (support alarm triggering by specified target types (human and vehicle)),video tempering alarm, exception |
| Linkage | Upload to FTP/memory card, notify surveillance center, send email, trigger capture, audible warning, Flashing Light |
| General | |
| Power | 12 VDC ± 25%, 0.66 A, max. 8 W,Ø5.5 mm coaxial power plug,reverse polarity protection, PoE: IEEE 802.3af, Class 3, max. 9.5 W |
| Material | PLASTIC & METAL |

Flashing Light

Yes

PCNS Kathmandu-10, Baneshwor, Nepal info@pcns.com.np +977 9700045888

